



Product Information

COBRA ALPLEX HD BEARING GREASE MP-3

COBRA ALPLEX HD BEARING GREASE MP-3 is a Heavy Duty and High-Quality Aluminum Complex Multipurpose Grease, specially formulated with premium base oils, and specially selected-High-Quality additives.

APPLICATIONS COBRA ALPLEX HD BEARING GREASE MP-3 suitable for applications in Ball Bearing continuously exposed to high temperatures up to +180°C. Through the use of ALUMINUM COMPLEX additive, our grease sets out to limit high oxidation, especially suited for elevated temperature working condition. Unique advantages include excellent protection against bearing wear, rust and corrosion, with super high resistance to water wash-out.

- BENEFITS**
- Heavy Duty Bearing Grease Enchanted with Superb Resistance to Water Wash-out.
 - Outstanding Protection Against Bearing Wear, Rust and Corrosion.
 - Minimum Dropping Point at 274°C.
 - Multipurpose Grease for Wide Range of Applications, with High Mechanical and Chemical Stability.
 - Extends Grease Life and Enhances Bearing Protection.
 - Excellent Surface Adhesion.
 - Exceptional Performance Over Wide Temperature Range.

TYPICAL PROPERTY

CHARACTERISTIC	METHOD	RESULTS
Thickener		Aluminum Complex
Color		Light Brown Transparent
Texture		Smooth
NLGI Consistency		3
Penetration Point at 25°C (mm/10)	ASTM D-217	235
Dropping Point (°C)	ASTM D-2265	274
Copper Strip Corrosion at 100°C, 24Hr	ASTM D-4048	1b
4-Ball EP Test Welding Point (Kgf)	ASTM D-2596	160
4-Ball EP Test Wear Scar (mm)	ASTM D-2266	0.39

PACKAGING

24X1LB, 15KG





Informasi Produk

COBRA ALPLEX HD BEARING GREASE MP-3

COBRA ALPLEX HD BEARING GREASE MP-3 adalah Gemuk *heavy duty* dan *Aluminium Complex* serbaguna dan memiliki kualitas yang terbaik, diformulasikan khusus dengan bahan dasar oli premium dan aditif berkualitas tinggi.

PENGUNAAN

COBRA ALPLEX HD BEARING GREASE MP-3 cocok untuk diaplikasikan pada *ball bearing* yang terus menerus terkena suhu tinggi hingga +180°C. Melalui penggunaan aditif *Aluminium Complex*, Gemuk kami berfungsi membatasi oksidasi tinggi, sangat tepat untuk kondisi kerja bersuhu tinggi. Keunggulan uniknya mencakup perlindungan yang sangat baik terhadap bantalan keausan, karat dan korosi, dengan ketahanan super tinggi terhadap *water wash-out*.

KEUNGGULAN

- Gemuk *heavy duty* untuk *bearing* yang memiliki ketahanan luar biasa terhadap *water wash-out*.
- Perlindungan luar biasa terhadap keausan bantalan, karat, dan korosi.
- Titik *dropping* minimum pada 274°C.
- *Multipurpose Grease for Wide Range of Applications, with High Mechanical and Chemical Stability.*
- Memperpanjang umur Gemuk dan meningkatkan perlindungan pada *bearing*.
- Adhesi permukaan yang sangat baik.
- Performa luar biasa pada rentang temperatur luas.

TYPICAL PROPERTY

CHARACTERISTIC	METHOD	RESULTS
Thickener		Aluminum Complex
Color		Light Brown Transparent
Texture		Smooth
NLGI Consistency		3
Penetration Point at 25°C (mm/10)	ASTM D-217	235
Dropping Point (°C)	ASTM D-2265	274
Copper Strip Corrosion at 100°C, 24Hr	ASTM D-4048	1b
4-Ball EP Test Welding Point (Kgf)	ASTM D-2596	160
4-Ball EP Test Wear Scar (mm)	ASTM D-2266	0.39

KEMASAN

24X1LB, 15KG

